

119 Series Ceiling Fixture Specifications

T6 Circline Lamps – 10,000 hours lamp life, 50,000 hours ballast life

Item Number	Description	Ballast Wattage	Lamp Wattage	Incandescent Wattage Comparison	Initial Lumens	Input Line Current	Replacement Lamp	Replacement Ballast
11930PB ★	14" Polished Brass Step Base w/ Plastic Swirl Cover	30	30	120	2000	.44A	32030	17030Q



★ = Energy Star

Specifications (at full brightness)

End of Life Protection	Yes
Ballast Type	Electronic
Starting Method	Modified Rapid Start
Input Line Voltage	120VAC
Input Line Frequency	50/60HZ
Lamp Life (rated)	10,000 Hours
Ballast Life (rated)	50,000 Hours
Color Temperature	2850° K
Color Rendering Index	84
Minimum Starting Temperature	-20 ° F
Maximum Operating Temperature	160 ° F
U.L. / C.U.L. Listed	Yes
FCC Compliance	Part 18, Subpart C
Lamp Operating Frequency	45 KHZ
Lamp Current Crest Factor	< 1.60
Maximum Open Circuit Voltage	600V
Power Factor	> .50
Total Harmonic Distortion	< 150%

Applications

- Use anywhere a standard incandescent fixture is used
- Use in bedroom, hallways, kitchens, living rooms, and rec rooms

Features and Benefits

- Long life, 10,000 hour average rated bulb life 50,000 hour average rated ballast life
- Bulb lasts 7 years, based on 4 hours use per day
- Bulb lasts 10 times longer than similar incandescent bulbs
- 2850°K color temperature closest to incandescent light
- Quick run-up time
- Instant start, flicker free
- Replaceable Ballast, Snap-in / No wiring
- World class phosphor insures high lumen output and excellent lumen maintenance
- UL Lamp Location Rated



ISO 9002
CERTIFIED

2 YEAR
WARRANTY