


GU Outdoor Porch Fixture Specifications

13W, 18W, 23W GU24 Lamps – GU24 Base, NPF Compact Fluorescent, 10,000 Hours Lamp life

Item Number	Watts	Description	Initial Lumens	Height (Inches)	Width (Inches)	Depth (Inches)	Replacement Lamp
56309BPCGU	9	Wall Mount, Black, Jelly Jar Diffuser w/ Photocell	600	9.45	5.75	4.4	33109SP
56309WPCGU	9	Wall Mount, White, Jelly Jar Diffuser w/ Photocell	600	9.45	5.75	4.4	33109SP
56409BPCGU	9	Ceiling Mount, Black, Jelly Jar Diffuser w/ Photocell	600	9.65	4.75	4.75	33109SP
56409WPCGU	9	Ceiling Mount, White, Jelly Jar Diffuser w/ Photocell	600	9.65	4.75	4.75	33109SP
56313BPCGU ★	13	Wall Mount, Black, Jelly Jar Diffuser w/ Photocell	900	9.45	5.75	4.4	33113SP
56313WPCGU ★	13	Wall Mount, White, Jelly Jar Diffuser w/ Photocell	900	9.45	5.75	4.4	33113SP
56413BPCGU ★	13	Ceiling Mount, Black, Jelly Jar Diffuser w/ Photocell	900	9.65	4.75	4.75	33113SP
56413WPCGU ★	13	Ceiling Mount, White, Jelly Jar Diffuser w/ Photocell	900	9.65	4.75	4.75	33113SP
56318BPCGU ★	18	Wall Mount, Black, Jelly Jar Diffuser w/ Photocell	1200	9.45	5.75	4.4	33118SP
56318WPCGU ★	18	Wall Mount, White, Jelly Jar Diffuser w/ Photocell	1200	9.45	5.75	4.4	33118SP
56418BPCGU ★	18	Ceiling Mount, Black, Jelly Jar Diffuser w/ Photocell	1200	9.65	4.75	4.75	33118SP
56418WPCGU ★	18	Ceiling Mount, White, Jelly Jar Diffuser w/ Photocell	1200	9.65	4.75	4.75	33118SP
56323BPCGU ★	23	Wall Mount, Black, Jelly Jar Diffuser w/ Photocell	1600	9.45	5.75	4.4	33123SP
56323WPCGU ★	23	Wall Mount, White, Jelly Jar Diffuser w/ Photocell	1600	9.45	5.75	4.4	33123SP
56423BPCGU ★	23	Ceiling Mount, Black, Jelly Jar Diffuser w/ Photocell	1600	9.65	4.75	4.75	33123SP
56423WPCGU ★	23	Ceiling Mount, White, Jelly Jar Diffuser w/ Photocell	1600	9.65	4.75	4.75	33123SP



★ = Energy Star

Specifications (at full brightness)

End of Life Protection.....	Yes
Ballast Type	Electronic
Starting Method	Modified Rapid Start
Input Line Voltage	120VAC
Input Line Frequency	50/60HZ
Lamp Life (rated)	10,000 Hours
Color Temperature	2700°K
Color Rendering Index	82
Minimum Starting Temperature	-20 ° F
Maximum Operating Temperature	160 ° F
U.L. / C.U.L. Listed	Yes
FCC Compliance	Part 18, Subpart C
Lamp Operating Frequency	45 KHZ
Lamp Current Crest Factor	< 1.60
Maximum Open Circuit Voltage	600V
Power Factor	>.50
Total Harmonic Distortion	< 150%
Dimming Range	N/A

Applications

- Use outdoors, mounts flush to a wall
- Perfect for: Porches, Door ways, Garages

Features and Benefits

- UL approved for wet locations
- Fixtures automatically include Photocell for dusk to dawn applications
- Long life, 10,000 hour average rated lamp life
- Lasts 7 years, based on 3 hours use per day
- Lasts 10 times longer than similar incandescent
- Quick run-up time
- Instant start, flicker free
- World class phosphor insures high lumen output and excellent lumen maintenance

